



United States Patent [19]

Poutasse

[11] Patent Number:

6,132,851

[45] Date of Patent:

Oct. 17, 2000

[54] ADHESIVE COMPOSITIONS AND COPPER FOILS AND COPPER CLAD LAMINATES USING SAME

[75] Inventor: Charles A. Poutasse, Cleveland, Ohio

[73] Assignee: GA-TEK Inc., Eastlake, Ohio

[21] Appl. No.: 08/267,877

[22] Filed: Jun. 28, 1994

[51] Int. Cl. B32B 3/00 [52] U.S. Cl. 428/209; 428/408; 428/413;

428/417; 428/418; 428/446; 428/457; 428/901; 525/109; 525/113

209, 408, 413, 417, 418, 252, 444, 457, 446, 409; 156/64

[56]

References Cited

U.S. PATENT DOCUMENTS

3,496,130	2/1970	Wasem et al 260/26
3,935,053	1/1976	Armstrong 156/64
4,020,225		Fujiwara 428/901
4,246,162	1/1981	Schreiber 260/37
4,343,843		Johnson 428/272
5,061,550		Shimizu 428/209
5.071.914		Zimmel 525/113

FOREIGN PATENT DOCUMENTS

0012714	6/1980	European Pat. Off.
0148493	8/1986	European Pat. Off.
0371242	6/1990	European Pat. Off.
62-101674	5/1987	Japan .


OTHER PUBLICATIONS


Search Report for European Appl. 95304380.9. Epoxy Resins, Chem. & Tech., May, 8, 1989 Marcel Dekker Inc., pp. 683-691, 1089-1095.

Primary Examiner—William Krynski Attorney, Agent, or Firm—Michael A. Centanni

[57] ABSTRACT

This invention relates to an adhesive composition, comprising: (A) at least one phenolic resole resin; and (B) the product made by reacting (B-1) at least one difunctional epoxy resin, with (B-2) at least one compound represented by the formula





wherein in Formulae (I) and (II): G, T and Q are each independently functional groups selected from the group consisting of COOH, OH, SH, NH₂, NHR¹, (NHC(=NH))_mNH₂, R²COOH, NR¹₂, C(O)NHR¹, R²NR¹₂, R²OH, R²SH, R²NH₂ and R²NHR¹, wherein R¹ is a hydrocarbon group, R² is an alkylene or alkylidene group and m is a number in the range of I to about 4; T can also be R¹, OR¹ or SO₂C₆H₄—NH₂; and Q can also be H. The invention also relates to copper foils having the foregoing adhesive composition adhered to at least one side thereof to enhance the adhesion between said foils and dielectric substrates. The invention also relates to laminates comprising copper foil, a dielectric substrate, and an adhesion-promoting layer comprising the foregoing adhesive composition disposed between and adhered to the foil and the substrate.

19 Claims, No Drawings